## **Listing of Claims:**

Claim 1. (Currently Amended) A torque distribution control device for a four-wheel drive vehicle having a torque transmission clutch for distributing the torque transmitted from an engine to prime drive wheels[[,]] and to sub-drive wheels, said control device comprising:

pre-torque operation means for determining a pre-torque to be transmitted to said subdriv sub-drive wheels based on a vehicle speed, a throttle opening degree and the gear shift step of a transmission;

compensation torque operation means for determining a compensation torque based on the rotational speed difference between said prime drive wheels and said sub-drive wheels; and

command torque operation means for determining a command torque by the addition of said pre-torque and said compensation torque;

wherein said torque transmission clutch is controlled based on said command torque input from said command torque operation means.

Claim 2. (Currently Amended) A torque distribution control device as set forth in claim 1, wherein said compensation torque operation means determines said compensation torque based on said rotational speed difference between said prime drive wheels and said sub-drive sub-driv wheels and said vehicle speed.

Claim 3. (Original) A torque distribution control device as set forth in claim 1, wherein said pre-torque operation means is provided with plural pre-torque maps on each of which various pre-torques to be transmitted to said sub-drive wheels are set based on various vehicle speeds and various throttle opening degrees, respectively for the gear shift steps of said transmission, and wherein said pre-torque operation means determines said pre-torque by

the selection of one of said plural pre-torque maps corresponding to a selected one of said gear shift steps.

Claim 4. (Currently Amended) A torque distribution control device as set forth in claim 1, wherein said pre-torque operation means is provided with a pre-torque map on which various pre-torques to be transmitted to said sub-drive wheels are set based on various vehicle speeds and various throttle opening degrees, for at <u>least l-ast</u> one gear shift step of said transmission, and wherein said pre-torque operation means performs a modification operation so that said pre-torque determined from said pre-torque map based on said vehicle speed and said throttle opening degree is modified in dependence on the difference between said one gear shift step and a selected gear shift step.

Claim 5. (Currently Amended) A torque distribution control device as set forth in claim 1, wherein said pre-torque operation means determines said pre-torque to be transmitted to said sub-drive wheels based on said vehicle speed calculated from wheel speeds which are detected by wheel speed sensors, said throttle opening degree detected by a throttle throttl sensor, and said gear shift step detected by a gear position sensor.

Claim 6. (Currently Amended) A torque distribution control device as set forth in claim 1, wherein said torque distribution device is provided with transmission clutch is an electromagnetic clutch for distributing said torque transmitted from said engine to said prime wheels to said sub-drive wheels; and , further comprising a current control circuit for applying to an electromagnetic coil of said electromagnetic clutch a command current which is necessary for said electromagnetic clutch to transmit said command torque to said sub-drive wheels.

Claim 7. (Currently Amended) A torque distribution control device for a four-wheel drive vehicle having a torque transmission clutch for distributing the torque transmitted from an engine to prime drive wheels[[,]] and to sub-drive wheels, said control device comprising:

pre-torque operation means for determining a pre-torque to be transmitted to said subdrive wheels based on a vehicle speed and a throttle opening degree;

compensated pre-torque operation means for compensating said pre-torque based on said throttle opening degree and the acceleration/deceleration of said vehicle;

feedback torque operation means for determining a feedback torque based on the rotational speed difference between said prime drive wheels and said sub-drive wheels;

command torque operation means for calculating a command torque by the addition of said compensated pre-torque and said feedback torque;

wherein said torque transmission clutch is controlled based on said command torque.

Claim 8. (Currently Amended) A torque distribution control device as <u>set</u> s-t forth in claim 7, wherein said feedback torque operation means determines said feedback torque based on said rotational speed difference between said prime drive wheels and said sub-drive wheels and said vehicle speed.

Claim 9. (Currently Amended) A torque distribution control device as set forth in claim 7, further comprising compensation torque operation means for determining a compensation torque <u>based</u> based on said throttle opening degree and said acceleration/deceleration of said vehicle, wherein said compensated pre-torque operation means calculates said compensated pre-torque by adding said compensation torque to said pre-torque.

Application No. 10/695,991 Reply to Office Action of January 12, 2005

Claim 10. (Currently Amended) A torque distribution control device as set forth in claim 7, wherein said compensated pre-torque operation means determines said compensated pre-torque by multiplying said pre-torque with a coefficient which is set in dependence on said throttle throttl opening degree and said acceleration/deceleration of said vehicle.

Claim 11. (Currently Amended) A torque distribution control device as set forth in claim 7, wherein said torque transmission clutch is constituted by an electromagnetic clutch, said control device further including electric current application means for applying a command electric current, which is necessary for said electromagnetic clutch to transmit said command torque, to an electromagnetic coil of said electromagnetic clutch.

28